

# S-SERIES

## BENCH-TOP DUCTED FUME CUPBOARD

**bypass top grid** to ensure constant face velocity

(CAV: constant air volume)

aerodynamic uprights and sash handle for **best containment**

**transparent PVB glass** for long-lasting chemical resistance



### FEATURES /

LARGE RANGE OF POLYPROPYLENE REMOTE EXTRACTION FANS FOR ALL APPLICATIONS (ATEX AVAILABLE)- SINGLE PHASE 220V OR THREE PHASE 380V  
COUNTERWEIGHTED FRONTAL SASH WITH WIRE ROPE FAILURE TOLERANCE  
INTERNAL BACK AND TOP BAFFLE FOR BEST SUCTION

#### CERTIFIED TO:

BS7258/1994 - EN14175-3 - DIN12924 - ANSI ASHRAE 110

# S -SERIES BENCH-TOP DUCTED FUME CUPBOARD

## FEATURES

- Aluminium extruded uprights and epoxy-polyester powder painted steel frame
- **Counterweighted sash and lateral sides** made in 6 mm thickness **safety glass (PVB)**
- Back and top baffle in **acid-resistant** 5 mm thickness HPL laminate.
- **Stainless steel worktops** with fluid containment rims



### S 1000

External dim.(mm)	1000x750x1500
Internal dim. (mm)	950x600x1150
Max. working opening (mm)	780x400
Max. sash opening (mm)	780x720
Lighting (220V/50Hz-IP67)	2x18W
Weight	100 kg
Package dim. (mm)	1200x800x1600

### S 1200

External dim.(mm)	1200x750x1500
Internal dim. (mm)	1150x600x1150
Max. working opening (mm)	980x400
Max. sash opening (mm)	980x720
Lighting (220V/50Hz-IP67)	2x18W
Weight	120 kg
Package dim. (mm)	1400x800x1600

### S 1500

External dim.(mm)	1500x750x1500
Internal dim. (mm)	1450x600x1150
Max. working opening (mm)	1280x400
Max. sash opening (mm)	1280x720
Lighting (220V/50Hz-IP67)	2x36W
Weight	150 kg
Package dim. (mm)	1600x800x1600

### S 1800

External dim.(mm)	1800x750x1500
Internal dim. (mm)	1750x600x1150
Max. working opening (mm)	1580x400
Max. sash opening (mm)	1580x720
Lighting (220V/50Hz-IP67)	2x36W
Weight	170 kg
Package dim. (mm)	2000x800x1600



IP 65 FLUORESCENT LAMP



INOX WORKTOP - HPL LAMINATE BACK BAFFLE



AERODYNAMIC PROFILES

- Stands or benches with ventilated under-bench key-locked storage
- Trolleys for mobility with antistatic wheels
- Antivibration base-stands for weighing using high-precision balances
- Polypropylene or monolithic ceramic (stone wear) worktops
- Different dimension sinks and drip cups
- Electrical plugs
- Gas and water services
- IP65 power-box with start/stop remote control switch, circuit breaker for overload protection with adjustable amperage for remote extractor fan supply
- Formalin dispensing kits with carboys, pumps and spigot
- Internal UV light IP67
- Magnifying lens with light
- Spot light for precision operations
- Shelf for containers hung to back baffle

## Gruppo Strola sas

Via Carlo Pittara 52  
10151 Torino - ITALY  
Tel +39 0117390860  
Fax +39 0114558763  
info@gruppostrola.com  
www.gruppostrola.com

## ACCESSORIES